

Filtration Products

Column Couplers	18
Filter Membranes	15
Inlet Filters	
Metal-free / Biocompatible.....	16
Stainless Steel	16
In-Line Filters	
Biocompatible PEEK	17 - 18
Stainless Steel	17 - 18
Mobile Phase Filtration Accessories	13 - 14
Mobile Phase Filtration System	13
Solvent Pickup Adapter	14
Solvent and Waste Protection	14
Syringe Filters	
Non-Sterile	10 - 12
Sterile	12
Syringes, Disposable.....	12



“ We have found your syringe filters to be **competitively priced** and well made compared with our usual brand. They don't seem to clog as quickly and there is no loss of performance for our sample prep, usually 2mL vials of Pharmaceutical active ingredients. ”

Wes Herridge
Laleham Healthcare, UK

The opinions stated herein are solely those of the speaker and not necessarily those of any company or organization.

Phenex LC/GC Approved Syringe Filters

For sample and solvent filtration prior to chromatography



- Rapid filtration of LC and GC samples prior to analysis
- Particulate, PVC, and extractable-free filters
- Less system downtime
- More consistent, reproducible results
- Increased column lifetime

Phenex Offers:

- Broad chemical compatibility
- Minimized extractables
- Excellent flow rate
- High total throughput
- Certified quality
- 100 % integrity tested
- Low hold-up volume
- Low protein adsorption
- Bi-directional use

Syringe Filter Selection Guide

1. Choose filter diameter based on sample volume

≤ 2 mL Sample Volume

4 mm Diameter

2 - 10 mL Sample Volume

15 mm Diameter

10 - 100 mL Sample Volume

25 - 28 mm Diameter

2. Choose a pore size based on the nature of your sample and chromatographic method

Sample Description	Recommended Filter Pore Size
General aqueous or mixed organic samples prior to LC analysis with columns packed with > 3 µm particles. General clarification of GC, SFC, CE, and GPC samples.	0.45 µm
Viscous samples or samples containing high levels of particulate matter.	Glass Fiber Filter with 0.45 µm filter membrane
General aqueous or mixed organic samples prior to LC analysis with columns packed with ≤ 3 µm particles. Removal of fine particulate matter prior to GC, SFC, CE, and GPC samples.	0.20 µm
Gas samples prior to GC. Liquid samples prior to UHPLC or LC/MS. Other particulate-sensitive methods.	
Viscous samples such as serum, plasma or other biological matrices. Solutions with high particulate load such as some environmental, biofuels or food and beverage applications.	Glass Fiber Filter with 0.45 µm filter membrane

3. Choose a filter membrane according to the characteristics of your sample and filtering objective

Membrane Type	Recommended Uses
RC (Regenerated Cellulose)	Hydrophilic Regenerated Cellulose filter membranes are compatible with a very broad range of aqueous and mixed-organic solutions, making them one of the most universal filter materials used prior to chromatography. Phenex-RC filters also exhibit fast-flow and ultra-low protein and non-specific binding characteristics. Due to the beneficial material characteristics, Phenex-RC membranes are broadly recommended as an excellent general purpose/high-performance sample filter for most applications.
PTFE, Teflon™ (Polytetrafluoroethylene)	PTFE is an inherently hydrophobic membrane excellent for filtration of organic-based, highly acidic or basic samples and solvents. Widely used in chromatography, it is especially well suited for the clarification of non-aqueous samples. Although this membrane is hydrophobic, it can be made hydrophilic by wetting the membrane with alcohol and then flushing with deionized water.
PES (Polyethersulfone)	Polyethersulfone membranes exhibit very fast-flow and ultra-low protein binding characteristics and are ideally suited for use in many life science clarification applications. Phenex-PES membranes typically offer better chemical resistance than cellulose acetate and are broadly recommended for filtering critical biological samples, tissue culture media, additives and buffers.
NY (Nylon)	Nylon has inherent hydrophilic characteristics and works well for filtration of many aqueous and mixed-organic samples. In combination with a glass pre-filter (Phenex-GF/NY), this membrane is excellent for the filtration of particle-laden samples, such as foods and beverages, environmental, biofuels, and dissolution samples. For applications that require low protein or non-specific binding characteristics, Phenomenex recommends Phenex-RC (Regenerated Cellulose) filters.
CA (Cellulose Acetate)	Cellulose Acetate membranes exhibit ultra-low protein binding and are broadly used in the filtration of biological samples. In combination with a glass pre-filter (Phenex-GF/CA), this membrane is excellent for filtration of tissue culture media, general biological sample filtration and clarification.
PVDF (Polyvinylidene Fluoride)	Hydrophilic PVDF membrane provides high flow rates and throughput, low extractables, and broad chemical compatibility. This membrane binds less protein than nylon or PTFE membranes.
GF (Glass Fiber)	Glass Fiber (GF) filters are made of inert borosilicate glass and have a nominal 1.2 µm pore size. They are commonly used with highly viscous samples or samples that contain high concentrations of particulate matter (e.g., food analysis, biological samples, soil samples, fermentation broth samples, removal of yeasts, molds, etc.). Glass Fiber filters can be used alone or in series with other Phenex filter membranes such as the 0.45 µm pore Phenex-RC filter to reduce clogging of the membrane and optimize flow.

Filtration Syringe Filters

guarantee

If Phenex Syringe Filters do not perform as well or better than your current syringe filter product of similar membrane, diameter and pore size, return the product with comparative data within 45 days for a FULL REFUND.

Phenex™ Syringe Filters (cont'd)

Tip: Try a Sample Pack!

Request yours today by phone or visit www.phenomenex.com/sample



Ordering Information ¹ Phenex Syringe Filters		4 mm Diameter for ≤ 2 mL sample volumes		15 mm Diameter for 2 – 10 mL sample volumes		25 - 28 mm Diameter for 10 – 100 mL sample volumes	
Membrane Type/Size	Part No.	Unit	Part No.	Unit	Part No.	Unit	
RC (Regenerated Cellulose)	AF0-3203-12	100/pk	AF0-2203-12	100/pk	AF0-8203-12 ⁵	100/pk	
	AF0-3203-52	500/pk	AF0-2203-52	500/pk	AF0-8203-52 ⁵	500/pk	
PES ³ (Polyethersulfone)	—	—	—	—	AF0-8208-12 ⁷	100/pk	
	—	—	—	—	AF0-8208-52 ⁷	500/pk	
PTFE ⁶ (Polytetrafluoroethylene)	AF0-3202-12	100/pk	AF0-2202-12	100/pk	AF0-1202-12	100/pk	
	AF0-3202-52	500/pk	AF0-2202-52	500/pk	AF0-1202-52	500/pk	
NY (Nylon)	AF3-3207-12	100/pk	AF0-2207-12	100/pk	AF0-1207-12	100/pk	
	AF3-3207-52	500/pk	AF0-2207-52	500/pk	AF0-1207-52	500/pk	
0.20 µm GF/NY ² (Glass Fiber/Nylon)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a Nylon (NY) membrane. Excellent for filtration of particle-laden samples, such as foods and beverages, environmental, biofuels, and dissolution samples. Use less hand pressure to filter even the most difficult samples. Outlet connection is luer lock.				AF0-1A47-12 ⁷	100/pk	
					AF0-1A47-52 ⁷	500/pk	
PVDF (Polyvinylidene Fluoride)	—	—	AF6-5206-12 ⁸	100/pk	AF6-6206-12	100/pk	
	—	—	AF6-5206-52 ⁸	500/pk	AF6-6206-52	500/pk	
GF/PVDF (Glass Fiber/Polyvinylidene Fluoride)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a PVDF membrane. The hydrophilic PVDF membrane provides high flow rates and throughput, low extractables and broad chemical compatibility. This membrane binds less protein than nylon or PTFE membranes.				AF6-6C06-12	100/pk	
					AF6-6C06-52	500/pk	
CA ⁴ (Cellulose Acetate)	—	—	—	—	AF0-8204-12 ⁷	100/pk	
	—	—	—	—	AF0-8204-52 ⁷	500/pk	
GF/CA ^{2,3,4} (Glass Fiber/Cellulose Acetate)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a CA membrane. Excellent for filtration of tissue culture media, general biological sample filtration and clarification. Outlet connection is luer lock.				AF0-8A09-12 ⁷	100/pk	
					AF0-8A09-52 ⁷	500/pk	
RC (Regenerated Cellulose)	AF0-3103-12	100/pk	AF0-2103-12	100/pk	AF0-8103-12 ⁵	100/pk	
	AF0-3103-52	500/pk	AF0-2103-52	500/pk	AF0-8103-52 ⁵	500/pk	
PES ³ (Polyethersulfone)	—	—	—	—	AF0-8108-12 ⁷	100/pk	
	—	—	—	—	AF0-8108-52 ⁷	500/pk	
PTFE ⁶ (Polytetrafluoroethylene)	AF0-3102-12	100/pk	AF0-2102-12	100/pk	AF0-1102-12	100/pk	
	AF0-3102-52	500/pk	AF0-2102-52	500/pk	AF0-1102-52	500/pk	
NY (Nylon)	AF3-3107-12	100/pk	AF0-2107-12	100/pk	AF0-1107-12	100/pk	
	AF3-3107-52	500/pk	AF0-2107-52	500/pk	AF0-1107-52	500/pk	
0.45 µm GF/NY ² (Glass Fiber/Nylon)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a Nylon (NY) membrane. Excellent for filtration of particle-laden samples, such as foods and beverages, environmental, biofuels, and dissolution samples. Use less hand pressure to filter even the most difficult samples. Outlet connection is luer lock.				AF0-1B47-12 ⁷	100/pk	
					AF0-1B47-52 ⁷	500/pk	
PVDF (Polyvinylidene Fluoride)	—	—	AF6-5106-128	100/pk	AF6-6106-12	100/pk	
	—	—	AF6-5106-528	500/pk	AF6-6106-52	500/pk	
GF/PVDF (Glass Fiber/Polyvinylidene Fluoride)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a PVDF membrane. The hydrophilic PVDF membrane provides high flow rates and throughput, low extractables and broad chemical compatibility. This membrane binds less protein than nylon or PTFE membranes.				AF6-6D06-12	100/pk	
					AF6-6D06-52	500/pk	
GF/CA ^{2,3,4} (Glass Fiber/Cellulose Acetate)	An integrated syringe filter unit containing an inert borosilicate glass fiber prefilter and a CA membrane. Excellent for filtration of tissue culture media, general biological sample filtration and clarification. Outlet connection is luer lock.				AF0-8B09-12 ⁷	100/pk	
					AF0-8B09-52 ⁷	500/pk	
1.20 µm GF ^{2,3} (Glass Fiber)	Prefiltration of heavily contaminated or highly viscous samples. When used in-series preceding a membrane filter, clogging of the membrane filter is prevented and sample clean up is optimized. Outlet connection is luer lock.				AF0-8515-12 ⁷	100/pk	
					AF0-8515-52 ⁷	500/pk	



1. Larger quantity purchases at significant savings are available.
2. Glass fiber filters are 28 mm diameter and made of borosilicate. They will remove 90 % of all particles >1.2 µm.
3. Housing material is methacrylate butadiene styrene (MBS) polymerisate. Also known as Cyrolite®.

4. Cellulose acetate is surfactant-free.
5. 26 mm diameter.
6. Hydrophobic membrane. Can be made hydrophilic by pre-wetting with IPA.

7. 28 mm diameter.
8. 17 mm diameter.
9. Additional dimensions and membrane types are available. Please contact your local Phenomenex technical consultant or distributor for availability or assistance.



Above syringe filters are non-sterile. Housing is made of medical-grade polypropylene (PP), and offer luer lock inlet/slip outlet connections, unless otherwise indicated.

Filtration Syringe Filters and Disposable Syringes

Phenex™ Syringe Filters (cont'd)

Syringe Filter Applications and Recommended Membranes

Application / Sample	Recommended Filter	First Alternative	Second Alternative
LC and GC Sample Prep	RC	PTFE	PES
Aggressive or Pure Organic Solvents	PTFE	RC	NY
Protein Analysis / Biological Samples	PES	RC	GF/CA
High Particulate Loads	GF/NY	GF + RC	PTFE
Environmental Methods	GF/NY	RC	PTFE
Food and Beverage	GF/NY	RC	PTFE
Clinical Research / Toxicology	RC	PES	NY
Dissolution Testing	GF/NY	RC	PTFE
Ion Chromatography	RC	PES	PTFE
Trace Metals (ICP-MS, AAS)	RC	PES	NY
Capillary Electrophoresis (CE)	RC	PES	NY
Tissue Cultures, Media, Buffers	GF/CA	PES	RC

i For high load and particulate-laden samples you may consider placing a Glass Fiber (GF) prefilter, either integrated with the membrane as one unit (Phenex-GF/NY or -GF/CA) or in series with the membrane syringe filter of your choice.



Syringe Filter Finder
3-step tool designed to help you find the appropriate syringe filter to help you successfully remove particulates from your sample matrix.
www.phenomenex.com/SFfinder

Sterile Syringe Filters

Sterile syringe filters from Phenomenex are ready-to-use, individually blister packaged units, offering high flow rates at low inlet pressures, for rapid sterile filtration.



Ordering Information

Sterile Syringe Filters

Part No.	Pore Size (µm)	Disc Diameter (mm)	Membrane Material	Unit
AF0-8455	0.2	28	CA Luer/Slip	50/pk
AF0-8456	0.45	28	CA Luer/Slip	50/pk
AF0-8457	0.2	28	PES Luer/Slip	50/pk
AF0-8458	0.45	28	PES Luer/Slip	50/pk
AF0-8459	0.2	25	RC Luer/Slip	50/pk
AF0-8461	0.2	25	PTFE Luer/Slip	50/pk

All-Plastic Disposable Syringes

- Use for all syringe filter applications*
- Luer-lock outlet makes connection easy
- Made of ultra-clean, high-purity plastics



Ordering Information

All-Plastic Disposable Syringes


Part No.	Description	Capacity (mL)*	Unit
AS0-8408	Plastic Disposable Syringes, Luer-lock	3	100/pk
AS0-8409	Plastic Disposable Syringes, Luer-lock	5	100/pk
AS0-8410	Plastic Disposable Syringes, Luer-lock	10	100/pk
AS0-8411	Plastic Disposable Syringes, Luer-lock	20	100/pk

* Choose larger volume syringe to reduce force on syringe filter membrane. 10 mL syringe is recommended.

All-Glass Vacuum Mobile Phase Filtration System

FilterSys™

- Prevents pump and system component damage
- Rapid filtration of buffers, organics and corrosive liquids
- Removes damaging microparticulates and bacterial contaminants
- HPLC and GC solvent and sample filtration



WARNING: The apparatus should be used with a water aspiration line, not a true vacuum line, unless secured behind an appropriate safety shield.

Designed for rapid filtration of particulate matter from HPLC solvents, this unit is an excellent value. Protect your instrument and column from costly damage by clarifying all your HPLC solvents and buffer solutions before use. This vacuum filter assembly comes with a sample reservoir and receiving flask. A 47 mm diameter membrane filter is placed between the fritted-glass support base and the sample reservoir, secured in place by an aluminum clamp. The support base itself is connected to the receiving flask by a vacuum-tight ground-glass joint. Only low-extractable borosilicate glass and the membrane filter come into contact with the mobile phase. The vacuum hose connection is made above the filtration drip tip to prevent contamination from the vacuum line.

Recommended filter membranes: Nylon is a highly resistant material and can be used with almost all laboratory solvents. Since Nylon is hydrophilic, no prewetting of the filter is required. PTFE (Teflon™) membrane filters are excellent for organic or other aggressive solvent systems. Extremely low levels of extractables (plasticizers, contaminants, etc.) make this an excellent filter for trace analysis work. PTFE is hydrophobic, so it is not recommended for the filtration of aqueous solutions.

Ordering Information

Mobile Phase Filtration System

Part No.	Description	Unit
Complete Assembly		
AH0-1566	FilterSys, 47 mm, 300 mL funnel with 1 L vacuum flask	ea
AH0-3314	FilterSys, 47 mm, 500 mL funnel with 2 L vacuum flask	ea
AH0-3315	FilterSys, 47 mm, 1000 mL funnel with 4 L vacuum flask	ea
Component Parts		
AH0-1567	Fritted support base, 47 mm, 40/35 taper	ea
AH0-1568	Funnel, graduated, 300 mL, 47 mm	ea
AH0-3323	Funnel, graduated, 500 mL, 47 mm	ea
AH0-3324	Funnel, graduated, 1000 mL, 47 mm	ea
AH0-1569	1 liter filter flask, 40/35 taper	ea
AH0-3321	2 liter filter flask, 40/35 taper	ea
AH0-3322	4 liter filter flask, 40/35 taper	ea
AH0-1570	Aluminum clamp, 47 mm	ea
Filter Membranes		
AF0-0503	Nylon, 0.2 µm, 47 mm	100/pk
AF0-0504	Nylon, 0.45 µm, 47 mm	100/pk
AF0-0514	PTFE, 0.5 µm, 47 mm	100/pk



For compatible Solvent Pickup Adapter, see p. 14
For additional Filter Membranes, see p. 15



Verex™ Certified sample vials, inserts, caps, and seals are guaranteed to ensure problem-free, reproducible performance you can trust – all at competitive prices. See page 30

or Visit:

www.phenomenex.com/VialFinder

Solvent Reservoirs / Bottle Filter Cap

- Eliminates makeshift HPLC reservoir covers, such as aluminum foil, Parafilm®, etc.
- Neatly seals to prevent particulate contamination
- Minimizes solvent evaporation and gas absorption

A disposable filter (any size Luer lock Teflon™ or nylon syringe filter) on the pressure equalization port minimizes the reabsorption of dissolved gases and prevents particle contamination. These assemblies fit the standard screw cap bottles with 38 mm cap size. The 1/8 in. OD Teflon feed line from the cap attaches directly to the HPLC pump. All cap parts are compatible with most common HPLC solvents.



Ordering Information

Filter Cap			
Part No.	Description	Cap Size	Unit
AH0-1565	Filter Reservoir Cap	38 mm	ea

Solvent Reservoir and Reagent Bottles

- Popular 1 and 2 liter sizes, equipped with 3-way valve cap
- Low-leaching (low alkali), borosilicate glass
- Chemically inert, internal PTFE seal

These wide-mouth GL45 mobile phase reservoirs come in 1- and 2-liter sizes. The reservoirs have easy-to-read volumetric markings to indicate the amount of solvent remaining. The versatile 3-way valve cap supplied with each reservoir provides a totally-inert PTFE (Teflon®) seal against the solvents inside.



Ordering Information

Reservoir and Valve Cap Assembly*			
Part No.	Mfr. No.	Description	Unit
AH0-4142	3200	HPLC Reservoir, 1000 mL clear glass, GL45 wide-mouth, includes 3-way Valve Cap	ea
AH0-4143	3203	HPLC Reservoir, 2000 mL clear glass, GL45 wide-mouth, includes 3-way Valve Cap	ea

* Fittings not included. See p. 413 [AQ0-2950](#)

Increase Lab Safety with HPLC/UHPLC Solvent Protection SecurityCAP™

HPLC/UHPLC Solvent (Eluent) and Waste Protection

- **Safer Laboratory Work Environment**
Solvent vapors and gasses are restricted to the containers
- **Confidence During Quality and Safety Audits**
Eliminate aluminum foil or parafilm covering solvent bottles
- **Easy to Use**
No more twisting tubes during bottle exchange



SecurityCAP Mobile Phase Safety Caps and Filters

SecurityCAP Waste Safety Caps and Filters

Solvent Pickup Adapter

This glass adapter enables direct pickup of mobile phase solvent for filtration using the Phenomenex FilterSys™ (see previous page). Safe in-line filtration with the pickup adapter replaces the tedious and dangerous pour-and-wait funnel filtration method. Eliminate the possibilities of spilling solvents and breathing toxic vapors. Replacing the funnel adapter on the FilterSys unit, the 47 mm pickup adapter with flange holds the membrane filter in place on top of the fritted support base, which in turn is held by the aluminum clamp (not included). The pickup adapter draws solvent directly from the reagent bottle — the safest way to transfer and filter solvents. The adapter includes a 4 mm PTFE (Teflon) valve with 1/4 in. OD outlet, PTFE 90° elbow with compression fittings for 1/4 in. OD tubing, and 3 feet of 1/4 in. OD PTFE tubing.



Ordering Information

Solvent Pickup Adapter			
Part No.	Description	Unit	
AH0-2947	Mobile Phase Pickup Adapter, 47 mm	ea	



For Ordering and Additional SecurityCAP Information, see page 324

Additional Filtration Products

Regular sample filtration means:

- Less system downtime
- Fewer troubleshooting problems
- Improved results

Removal of particulate matter to sub-micron levels is critical before any drug, tox, or dirty environmental sample is injected into an HPLC, GC or mass spectrometer. Also, products that remove matrix components, interferents, and chemical garbage will improve your results. Check out the following useful products:

Mini-Index	Page No.
Filtration Products (General Laboratory)	
• Syringe filters	10 - 12
• Membrane filters and filtration apparatus	13 - 15
Solid Phase Extraction (SPE) devices	
• Tubes and well plates	48 - 72
• Vacuum manifolds	75 - 78
Column Protection devices	
• SecurityGuard	
• UHPLC/HPLC (2.1 to 4.6 mm ID)	331
• Analytical (2 to 8 mm ID)	326 - 330
• SemiPrep (9 to 16 mm ID)	328 - 330
• PREP (18 to 29 mm ID)	328 - 330
• PREP (30 to 49 mm ID)	328 - 330
• SFC (18 to 29 mm ID)	328 - 330
• SFC (30 to 49 mm ID)	328 - 330
• Inlet filters	
• Biocompatible PEEK	16
• Stainless steel	16
• In-line filters	
• Biocompatible PEEK	
Analytical	17
SemiPrep	18
• Stainless steel	
Analytical	17
Prep	18

Filter Membranes

Phenex™

- RC, Nylon, PTFE (Teflon™), and other membranes available
- Wide selection of membrane sizes

Phenex PTFE (Teflon) and Regenerated Cellulose (RC) membrane filters offer excellent chemical resistance to almost all laboratory solvents and samples. They do not introduce unwanted plasticizers or extractables into the sample or mobile phase. Since Regenerated Cellulose (RC) is hydrophilic, filtering of aqueous solvents is simple. No prewetting is required. PTFE is hydrophobic and so is not recommended for the filtration of aqueous solutions.



Ordering Information

Filter Membranes				
Part No.	Pore Size (µm)	Disc Diameter (mm)	Membrane Material	Unit
Nylon				
AF0-0500	0.45	13	Nylon	100/pk
AF0-0501	0.2	25	Nylon	100/pk
AF0-0502	0.45	25	Nylon	100/pk
AF0-0503	0.2	47	Nylon	100/pk
AF0-0504	0.45	47	Nylon	100/pk
PTFE				
AF0-0512	0.45	25	PTFE	100/pk
AF0-0514	0.45	47	PTFE	100/pk
Cellulose Acetate (CA)				
AF0-8436	0.45	25	CA	100/pk
AF0-8437	0.2	25	CA	100/pk
AF0-8438	0.45	47	CA	100/pk
AF0-8439	0.2	47	CA	100/pk
Regenerated Cellulose (RC)				
AF0-8440	0.45	13	RC	100/pk
AF0-8441	0.2	13	RC	100/pk
AF0-8442	0.2	25	RC	100/pk
AF0-8443	0.45	47	RC	100/pk
AF0-8444	0.2	47	RC	100/pk
Polyethersulfone (PES)				
AF0-8445	0.2	25	PES	100/pk
AF0-8446	0.45	25	PES	100/pk
AF0-8447	0.2	47	PES	100/pk
AF0-8448	0.45	47	PES	100/pk
Cellulose Nitrate Ester (MCE)*				
AF0-8454	0.45	47	MCE	100/pk



*MCE = Mixed Cellulose Esters
Above filter membranes are non-sterile.
Phenex is a trademark of Phenomenex.




For a useful Membrane Selection Guide, see p. 10

Inlet Filters

Stainless Steel

- Protects pumps and check valves
- Easy to replace
- Low cost

HPLC solvent inlet filters are used at the low pressure inlet side of the pump to help protect the check valves, injector and column from damaging particulate contamination. Solvent filters are constructed of Hastelloy Steel and are available for 1/16 in. ID and 1/8 in. ID tubing. Due to the large surface area of the cylindrical frit, virtually no backpressure or cavitation is developed. The filter is easily cleaned by backflushing or sonicating.



Ordering Information

Solvent Inlet Filters - Stainless Steel

Part No.	Description	Unit
AF0-0356	Solvent Inlet Filter, 2 µm, for 1/16 in. ID tubing	ea
AF0-0359	Solvent Inlet Filter, 2 µm, for 1/8 in. ID tubing	ea
ATO-2955	Teflon Tubing, 5 ft. L x 1/8 in. OD x 1/16 in. (0.062 in.) ID	ea
ATO-2956	Teflon Tubing, 10 ft. L x 1/8 in. OD x 1/16 in. (0.062 in.) ID	ea
ATO-8609	Teflon Tubing, 5 ft. L x 1/4 in. OD x 1/8 in. (0.125 in.) ID	ea
ATO-8610	Teflon Tubing, 10 ft. L x 1/4 in. OD x 1/8 in. (0.125 in.) ID	ea



Important: Depending on the mobile phase, we recommend that you change your inlet filter every one to six months.




For disposable Syringe Filters offering convenient and economical sample and solvent filtration, see pp. 10 - 12

Metal-Free/Biocompatible

- Biocompatible
- Flat bottom design uses all available mobile phase
- High surface area for long filter life

The Solvent Saver™ Inlet Filter Unit utilizes a flat filter element that sits parallel to the bottom of the HPLC reservoir. The design allows the filter to draw all but the last 2 % of the mobile phase from the reservoir without drawing air into the system.

The Solvent Saver Inlet Filter is manufactured by pressing a PEEK filter element into an inert Teflon™ housing. The top of the housing has female 1/4 in.-28 threads to accept 1/8 or 1/16 in. OD tubing via PEEK flangeless fittings and Tefzel® ferrule (sold separately) or direct connect various size tubing using the Unifit adapter (sold separately). The Unifit adapter slip-fits onto 1.5, 2.2 or 3.0 mm ID tubing. This filter is excellent for sensitive biochromatography and ion chromatography applications where metal surfaces may corrode or interact with samples.



Ordering Information

Solvent Saver Inlet Filter - Metal-Free

Part No.	Description	Unit
AH0-1562	Solvent Saver Inlet Filter with 10 µm PEEK filter with Flangeless fitting for 1/8 in. OD tubing	ea
AQ0-8339	Solvent Saver Unifit Adapter, Tri-Step Tubing Connector, PEEK	ea
AQ0-2949	Flangeless Nut and Ferrule for 1/8 in. OD tubing, 1/4 in.-28 threads, red Delrin	10/pk
AQ0-2950	Flangeless Nut and Ferrule for 1/8 in. OD tubing, 1/4 in.-28 threads, green Delrin	10/pk
ATO-2953	Teflon Tubing, 5 ft. L x 1/16 in. OD x 1/32 in. (0.031 in.) ID	ea
ATO-2955	Teflon Tubing, 5 ft. L x 1/8 in. OD x 1/16 in. (0.062 in.) ID	ea
ATO-2956	Teflon Tubing, 10 ft. L x 1/8 in. OD x 1/16 in. (0.062 in.) ID	ea
ATO-8610	Teflon Tubing, 10 ft. L x 1/4 in. OD x 1/8 in. (0.125 in.) ID	ea

In-Line Filters

Stainless Steel (Analytical)

- Removes particulates from flow path
- Minimizes sample peak dispersion

In-line Filters are available to protect expensive HPLC columns from damaging microparticulates. Using one of these filters between the injection valve and the column is recommended for all HPLC systems. The 3 mm diameter filter element is recommended for use with conventional 4.6 mm diameter columns. Column In-line Filters are supplied with two 6 cm L x 0.007 in. ID connecting tubes. Pressure rating is 5000 psi (345 bar).



Ordering Information


Stainless Steel In-Line Filters (Analytical)

Part No.	Description	Unit
AF0-0377	In-line Filter with 0.5 µm Porosity x 3 mm dia. filter	ea
AF0-0378	Replacement Filter Disks: 0.5 µm x 3 mm	5/pk

Metal-Free/Biocompatible (Analytical)

- Biocompatible
- Virtually no band broadening or peak distortion
- Easy fingertight connection

This in-line filter assembly removes fine particles from the solvent stream without adding band broadening or peak distortion to your separation. Microparticulates down to 0.5 µm are effectively removed before they have a chance to plug your column and degrade your separation. The Polyglas™ frit with fluoropolymer frit assembly design is fully biocompatible and easily installed using fingertight connections. Pressure-rated to 5000 psi (345 bar).



Ordering Information

Metal-Free/Biocompatible In-Line Filter (Analytical)

Part No.	Description	Unit
AF0-1736	In-line Filter, 0.5 µm Frit	ea

KrudKatcher™

- Universal fit to virtually all manufacturers' analytical columns
- Saves expensive columns and equipment from damaging microparticulates
- Convenient, disposable in-line filter

There are two types of KrudKatchers depending on system backpressure and dead volume demands: the KrudKatcher Classic and the KrudKatcher Ultra.

Whereas conventional in-line filters typically cost much more and often require replacement parts and tools, the KrudKatcher is a simple, low-cost unit that is easily replaced and discarded when the backpressure indicates clogging or excessive particle build up. The universal connection is compatible with all standard 1/16 in. 10-32 internal threaded end-fittings used in columns, guard columns, injector valves, and other LC equipment.

The KrudKatcher Classic:

- Pressure-rated to **5000 psi (345 bar)**
- Hand-tightened connection



The PEEK filter body of the KrudKatcher Classic houses an integrated 0.5 µm 316 stainless steel depth filter that efficiently removes microparticulates from the flow stream with minimal contributions to system dead volume (2 µL).

Ordering Information

KrudKatcher Classic Disposable In-Line Filter (Analytical)

Part No.	Description	Unit
AF0-8497	KrudKatcher Disposable Pre-Column Filter, 0.5 µm	10/pk

The KrudKatcher Ultra:

- Fits virtually all UHPLC / HPLC columns 1.0 to 4.6 mm ID
- Pressure rated to **20000 psi (1375 bar)**
- Extremely low dead volume minimizes sample peak dispersion




The KrudKatcher Ultra filter body houses an integrated 0.5 µm 316 stainless steel depth filter that efficiently removes microparticulates from the flow stream without contributing to system backpressure or dead volume (<0.2 µL).

Ordering Information

KrudKatcher Ultra In-Line Filter (Analytical)

Part No.	Description	Unit
AF0-8497	HPLC KrudKatcher Ultra Column In-Line Filter, 0.5 µm Depth Filter x 0.004 in. ID	3/pk

KrudKatcher Ultra requires 3/16 in. wrench. Wrench not provided. See p. 417

 For SecurityGuard™, the universal guard cartridge system, see p. 326



If KrudKatcher in-line filters do not perform as well or better than your current in-line filter product of similar size, return the product with comparative data within 45 days for a FULL REFUND.

In-Line Filters (cont'd)

Metal-Free/Biocompatible (SemiPrep)

- For columns 8 to 18 mm ID
- Effective pre-column filtration
- Replaceable filter element



Phenomenex's Biocompatible SemiPrep in-line filter holder with replaceable filter element (2 µm PEEK frit) will help protect your column investment by safely removing particulate matter and insoluble material from the mobile phase and sample matrix. The filter consists of a stainless steel body, two PEEK end-fittings, and a separate PEEK frit. When you need to replace the filter, simply unscrew the assembly, remove the frit and replace it. This filter unit can be placed in the flow path before or after the column with little or no effect on peak shape. Pressure rated to 6000 psi (414 bar).

Ordering Information

Metal-Free/Biocompatible In-Line Filter (SemiPrep)

Part No.	Description	Unit
AF0-8420	HPLC SemiPrep Column In-Line Filter 2.0 µm Porosity x 10 mm dia. filter, Biocompatible	ea
AF0-8428	Replacement In-Line Filter Disk, PEEK, 2.0 µm Porosity x 10 mm dia.	5/pk

Stainless Steel (PREP)

- Economical protection for preparative HPLC columns and injectors
- For columns 19 to 30 mm ID
- Replaceable filter element

Preparative columns and the HPLC systems on which they are used are costly and must be protected against fouling. Phenomenex's PREP In-line Filter holder with replaceable filter element (2 µm stainless steel frit) will help protect your investment by safely removing particulate matter and insoluble material from the mobile phase and sample matrix. The filter unit can be placed in the flow path before or after the column with little or no effect on peak shape. This versatile filter can also protect check valves, injectors and detectors. Pressure rated to 8000 psi (551 bar).



Ordering Information

Stainless Steel In-Line Filters (PREP)

Part No.	Description	Unit
AF0-7866	HPLC PREP Column In-line Filter, S.S., 2.0 µm Porosity x 21.2 mm dia.	ea
AF0-7867	Replacement In-Line Filter Disks, S.S., 2.0 µm Porosity x 21.2 mm dia.	5/pk
AQ0-7877	PREP Replacement O-Rings, 1 in. OD x 7/8 in. ID x 1/16 in. CS, Fluorocarbon	2/pk
AT0-0465	Capillary S.S. Tubing, 0.020 in. ID x 0.062 in. (1/16 in.) OD x 10 cm L	5/pk
AT0-0466	Capillary S.S. Tubing, 0.020 in. ID x 0.062 in. (1/16 in.) OD x 20 cm L	5/pk

Analytical Column Couplers

Sure-Lok™ Coupler

- Universal and reusable
- Solvent resistant material
- Low dead-volume connection
- Compatible with all 10-32 internal-threaded fittings

Applications:

- Filter to column
- Column to column
- Precolumn to column
- Column to detector



Sure-Lok Coupler (PEEK)

Sure-Lok Couplers contain two Sure-Lok male nuts at either end of a 5 cm long 1/16 in. tubing. The PEEK biocompatible coupler has all parts composed of PEEK, including the 0.010 in. ID tubing. Fingertight to 5000 psi (345 bar).

Ordering Information

Sure-Lok Couplers (Analytical to SemiPrep)

Part No.	Description	Unit
AQ0-1392	PEEK Sure-Lok Coupler	ea
AQ0-1393	PEEK Sure-Lok Coupler	10/pk

PREP Column Coupler



Ordering Information

PREP Column Coupler

Part No.	Description	Unit
AQ0-8376	PREP Coupler, Stainless Steel Tube, Nuts, and Ferrules 10-32 Threads, 1/16 in. OD x 0.030 in. ID	ea



Protect your column and equipment with Phenex™ Syringe Filters

Filtering your sample helps prevent column and frit blockage, undue wear on detectors, pumps, valves, injector seals, and abnormally high operating pressures. Non-filtered samples can also lead to non-reproducible results and significant instrument downtime. See page 10 or Visit:

www.phenomenex.com/SFfinder



For SecurityGuard™, the universal guard cartridge system, see p. 326